

ORDER FORM

ORDER esales@premierframes.co.uk

QUOTE esales@premierframes.co.uk

New Build Replacement Project

PLAN VIEW

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

.....

.....

POSTCODE

Delivery Date Req

Quotation Ref

FRONT ELEVATION

CRITICAL INFORMATION

***Required for structural snow / wind loading**

*Site Postcode

Roof Pitch (°)

Roof height restriction

Frame width

CUSTOMER NOTE: Please carefully read the insulated perimeter pelmet design guide before filling in order details.

HOW TO PLACE AN ORDER FOR CLASSIC ROOF:

LEFT ELEVATION

RIGHT ELEVATION

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
 - a) roof windows
 - or b) rectangular glazed panels.
4. Upon placement of your Classic Roof order, an order confirmation is generated which must be signed and emailed back.

Job No.:3598

Please sign and return to
SALES@PREMIERFRAMES.CO.UK

SIGNED

DATE

ORDER FORM

JOB REFERENCE

ROOF COLOUR	White	Deeplas	Mahogany	Light Oak	Rosewood	Bespoke RAL/BS Colour
External	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Internal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

INTERNAL PELMET

Specify with this order Upgrade with retro fit Standard Width (300-600mm) Other (600-1200mm)

Original roof job no. if applicable: Please state (mm):

ROOF INFORMATION

On Fascia* Below Fascia Full Height Walls

If fitting to a bungalow please indicate Soffit Depth
N.B. If order is retro fit then option of **on fascia** is the only option available.

CENTRAL LIGHTING PANEL

Please add

CORNICE

Style 1 Tier 2 Tier 3 Tier Curved

Colour White Matt Grey Deeplas RAL/BS Colour

CONSERVAFLASH

Soaker Only

BAR UNDERCLADDINGS

Standard (uPVC)

Yes

TOP CAPPINGS

Dome (uPVC)
 Aluminium
 Bevel

TIE BARS

White Tie Bar
 TBRK (If possible)
 Brass

EAVES BEAM

Standard (VAAAH)
 Structural (SEB)
 Gable beam
(MUST be used with Cornice)

If using SEB please indicate span and location of doors on drawing.

FASCIA CLADDING

'V' Groove PFTB (Default on glazed roofs & pelmet)
 Ultraselect SFB (With tapestry infill (SFT003) White only)
 One piece decorative fascia DFT (All roof colours as above)

CONSERVAGLASS OPTIONS - BLACK WARM EDGE SPACER

TIER 1 - CONSERVAGLASS

C'Glass SMG Blue C'Glass SMG Neutral
 C'Glass SMG Bronze C'Glass SMG Aqua

TIER 2

C'Glass 4S Blue C'Glass 4S Neutral
 C'Glass 4S Bronze C'Glass 4S Aqua

TIER 3

C'Glass SMG
Ultimate Blue

TIER 4

C'Glass SMG
Ultra83 Blue

POLYCARBONATE

Size 25mm 35mm

Colour Clear Opal Bronze Bronze / Opal Heatguard / Opal

UNGLAZED

Polycarb 25mm 35mm

Glass 24mm

ROTABOND SEALANT - MS POLYMER

White (NCGS001W) Black (NCGS001B) No. Tubes Req: N.B. For use with Conservaglass

ROOF VENTS AND MECHANISM (mark plan)

Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole

Chrome Manual Spindle Manual Spindle and pole

Electric motor with digital thermostat and rain sensor Electric motor and rocker switch

Electric motor with radio and remote control Electric motor with thermostat (AVTD002)

Electric without switch/thermostat (Motor only)

DECORATION

Cresting Renaissance Tudor Elizabethan Baroque Classic Low profile Aluminium

Finial Pikestaff Sceptre Ball Coronet Classic Low profile Aluminium

ANCILLARY EXTRAS

Please refer to the Classic Technical Guide.