

# ORDER FORM

**ORDER** e:sales@premierframes.co.uk

**QUOTE** e:sales@premierframes.co.uk

New Build       Replacement Project

**PLAN VIEW**

ACCOUNT No.

Company Name .....

Order Number .....

**JOB REFERENCE** .....

Company Contact .....

Telephone No. ....

Email .....

Delivery Address .....

.....

.....

**POSTCODE** .....

Delivery Date Req .....

Quotation Ref .....

**FRONT ELEVATION**

**CRITICAL INFORMATION**

**\*Required for structural snow / wind loading**

\*Site Postcode .....

Roof Pitch (°) .....

Roof height restriction .....

Frame width .....

**CUSTOMER NOTE: Please carefully read the Livingroof installation guide before filling in order details.**

**HOW TO PLACE AN ORDER FOR LIVINROOF:**

**LEFT ELEVATION**

**RIGHT ELEVATION**

1. Sketch plan & elevations.  
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
  - a) roof windows
  - or b) rectangular glazed panels.
4. Upon placement of your Livingroof order, an order confirmation is generated which must be signed and emailed back.

Job No.:3598

# ORDER FORM

JOB REFERENCE .....

## ROOF INFORMATION

- On Fascia     Below Fascia\*     Full Height Walls

If fitting to a bungalow please indicate Soffit Depth .....

\*N.B. **Below fascia** is always on boxgutters, 30mm frame add on is needed but not supplied.

## EAVES BEAM

- Standard (VAAAH)  
 Structural (SEB)  
 Gable beam  
(MUST be used with Cornice)

If using SEB please indicate span and location of doors on drawing.

## INTERNAL PELMET

- Specify with this order     Upgrade with retro fit     Standard Width (300-600mm)     Other (600-1200mm)

Original roof job no. if applicable: .....

Please state (mm): .....

## EXTERNAL PANEL

- U-Tec through colour composite (to match 7016)     Aluminium powder coated sandwich (to match 7016)

## CORNICE

- Style     1 Tier     2 Tier     3 Tier     Curved

- Colour     White     Urban Grey     Deeplas White     Landmark Green     Pure Cream     RAL/BS Colour .....
- RAL 9003,    RAL 7016,    INTERPON SC050E,    BS14C35,    RAL 1015,    .....
- GLOSS 80%    GLOSS 30%    GLOSS 80%    GLOSS 80%    GLOSS 30%     Gloss % .....

## CONSERVAGLASS OPTIONS - BLACK WARM EDGE SPACER

### TIER 1 - CONSERVAGLASS

- C'Glass SMG Blue     C'Glass SMG Neutral  
 C'Glass SMG Bronze     C'Glass SMG Aqua

### TIER 2

- C'Glass 4S Blue     C'Glass 4S Neutral  
 C'Glass 4S Bronze     C'Glass 4S Aqua

### TIER 3

- C'Glass SMG  
Ultimate Blue

### TIER 4

- C'Glass SMG  
Ultra83 Blue

## ROTABOND SEALANT - MS POLYMER

- Black (NCGS001B)    No. Tubes Req:.....  
N.B. For use with Conservaglass

## CONSERVAFLASH

- Soaker Only  
 Yes

## ROOF VENTS AND MECHANISM (mark plan)

- Brass     Manual Spindle     Manual Spindle and pole     Manual Spindle and telescopic pole  
Chrome     Manual Spindle     Manual Spindle and pole
- Electric motor with digital thermostat and rain sensor     Electric motor and rocker switch  
 Electric motor with radio and remote control     Electric motor with thermostat (AVTD002)  
 Electric without switch/thermostat (Motor only)

## ANCILLARY EXTRAS

### IMPORTANT NOTE 1

The installer is responsible for ensuring that where Livinroof is supported by means such as timber frame walls, the structure provides enough lateral support and resistance to wind uplift. Further guidance can be obtained through our system overview. Ultraframe cannot be responsible for the structural adequacy of any existing building work used as part of an overall conversion. While assistance is provided, ultimate responsibility to secure Building Regulations / approvals lies with the retail installer.

### IMPORTANT NOTE 2

U-Design is the final arbiter on price and specification decisions.

### IMPORTANT NOTE 3

The Livinroof components have been designed and manufactured to meet the specification of each individual job. Any significant on site modifications particularly relating to the repositioning of any structural members will invalidate the product's warranty and compromise the structures integrity. If adjustments are required due to site conditions please consult Ultraframe. Tie Bars / Tie Beams will be specified by Ultraframe and will appear on your confirmation. Always check the confirmation carefully.

Job No.:3598