

ORDER FORM

ORDER e: roofsales@ultraframe.co.uk

PLAN VIEW

QUOTE e: quotes@ultraframe.co.uk

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

.....

.....

POSTCODE

Delivery Date Req

FRONT ELEVATION

Quotation Ref

CRITICAL INFORMATION

***Required for structural snow / wind loading**

*Site Postcode

Roof Pitch (°)

Roof height restriction

Frame width

HOW TO PLACE AN ORDER FOR CLASSIC ROOF:

LEFT ELEVATION

RIGHT ELEVATION

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions. **Vital for when SEB or bolstered eaves is needed.**
3. Mark the preferred positions of any roof windows (vents)
4. Upon placement of your Classic Roof order, an order confirmation is generated which must be signed and emailed back.

Job No.:3598

Please sign and return to
roofsales@ultraframe.co.uk

SIGNED

DATE

ORDER FORM

ClassicTMroof

By Ultraframe

JOB REFERENCE

ROOF COLOUR	White	Deeplas	Grained Grey	Smooth Grey	Mahogany	Light Oak	Rosewood	Bespoke RAL/BS Colour
External	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Internal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

INTERNAL PELMET (when internal pelmet specified)

Standard Width (300mm) Other (300-1200mm)
Please State (mm):

On Fascia Below Fascia

If fitting to a bungalow please indicate Soffit Depth

EAVES BEAM

Structural (SEB) Bolstered Eaves
 Eaves flow (eaves beam trickle ventilation)

Show openings on roof drawings on page 1.
If using SEB or bolstered eaves, please indicate span and location of doors on drawing.

CORNICE

Style 1 Tier 2 Tier 3 Tier Curved
Colour White Matt Grey Deeplas RAL/BS Colour

DOWNPIPE

Round
 Square

CONSERVAFLASH

Yes

RIDGE

Classic Ridge
 Slimline Ridge (ONLY on 25° georgian roof)

TOP CAPPINGS

Dome (PVCu)
 Aluminium
 Bevel (PVCu)

BOX GUTTER OPTIONS:

165mm 165mm Chambered
 265mm Other, please state:.....

GLASS OPTIONS - WARM EDGE SPACER

	Tier 4	Tier 3	Tier 2	Tier 1	
Conservaglass	<input type="checkbox"/> Ultra86 Blue	<input type="checkbox"/> Ultimate Blue	<input type="checkbox"/> Blue 4S <input type="checkbox"/> Neutral 4S	<input type="checkbox"/> Std Blue <input type="checkbox"/> Std Neutral	<input type="checkbox"/> Std Bronze <input type="checkbox"/> Std Aqua
Celsius	<input type="checkbox"/> Celsius Elite	<input type="checkbox"/> Celsius One	<input type="checkbox"/> Celsius Clear		

POLYCARBONATE

Size 25mm 35mm
Colour Clear Opal Bronze Bronze / Opal Heatguard / Opal

UNGLAZED

Polycarb 25mm 35mm
Glass 24mm

ROTABOND SEALANT - MS POLYMER

Black (NCGS001B) No. Tubes Req:..... N.B. For use with Conservaglass

ROOF VENTS AND MECHANISM (mark plan)

Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole
Chrome Manual Spindle Manual Spindle and pole
 Electric motor with digital thermostat and rain sensor Electric motor and rocker switch
 Electric motor with radio and remote control Electric motor with thermostat (AVTD002)
 Electric without switch/thermostat (Motor only)

DECORATION

Cresting Renaissance Tudor Elizabethan Baroque Classic Low profile Aluminium
Finial Pikestaff Sceptre Ball Coronet Classic Low profile Aluminium

ANCILLARY EXTRAS

Please refer to the Classic Technical Guide.

Job No.:3598

Please sign and return to
roofsales@ultraframe.co.uk

SIGNED

DATE